SAFETY DATA SHEET



1. Identification

Product identifier FireDefender® Expanded Perlite

Other means of identification None.

Recommended use Material Filler
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company nameGeorgia-Pacific Gypsum LLCAddress133 Peachtree Street, NE

Atlanta, GA 30303

Telephone Technical Information 800.225.6119

(M)SDS Request 404.652.5119

E-mail MSDSREQ@GAPAC.COM

Emergency phone number Chemtrec - Emergency 800.424.9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsEye irritationCategory 2B

Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 1 (lung)

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements





Signal word Danger

Hazard statement Causes eye irritation. May cause respiratory irritation. May cause cancer. Causes damage to

organs (lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke

when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention. Specific treatment (see

section 4 on the SDS).

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store away from

incompatible materials (see Section 10 of the SDS).

Disposal Dispose of contents/container in accordance with applicable regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Material name: FireDefender® Expanded Perlite
5384 Version #: 04 Revision date: November-05-2018 Issue date: October-16-2015

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------------|--------------------------|------------|-------------|
| CRYSTALLINE SILICA (QUARTZ) | | 14808-60-7 | 0 - < 2 |
| EXPANDED PERLITE | | 93763-70-3 | Up to - 100 |

The specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eye contact

contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

Exposed individuals may experience eye tearing, redness, and discomfort. Dusts may irritate the respiratory tract, skin and eyes. Causes eye irritation. Coughing. Discomfort in the chest.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

(show the label where possible). Ensure that medical personnel are aware of the material(s)

develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

Symptoms may be delayed. treatment needed

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

Shortness of breath. Prolonged exposure may cause chronic effects.

involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Sweep up or gather material and place in appropriate container for disposal. Minimize dust generation and accumulation. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

Avoid discharge into drains, water courses or onto the ground. If large quantities enter a waterway, **Environmental precautions** advise local authorities.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| 0.05 mg/m3 | Respirable dust. |
|------------|------------------|
| 0 | .05 mg/m3 |

US. ACGIH Threshold Limit Values

| Components | Туре | Value | Form | |
|--|------|-------------|----------------------|---|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. | • |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Туре | Value | Form | |
|--|------|------------|------------------|--|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | TWA | 0.05 mg/m3 | Respirable dust. | |
| EXPANDED PERLITE (CAS 93763-70-3) | TWA | 5 mg/m3 | Respirable. | |
| | | 10 mg/m3 | Total | |

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

When using product, provide local and general exhaust ventilation to keep airborne dust

concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of

dust.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses or goggles are recommended when using this product. Ensure compliance with

OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Safety

shower/eye wash fountain must be readily available in the workplace area (29 CFR 1910.151(c)).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Impervious protective clothing and gloves recommended to prevent drying or irritation of skin.

Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR

1910.151 (c)).

Respiratory protection A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or

when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection

(Z88.2).

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Keep away from food and drink. Always observe good personal hygiene measures, such as

considerations washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder.

Color White to off-white

Odor Odorless.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

Not available.

Not available. Flash point **Evaporation rate** Not available.

Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. Viscosity

Other information

Explosive properties Not explosive. Not oxidizing. **Oxidizing properties**

pH in aqueous solution 6 - 10 @ 10% Solution

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Acids.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Incompatible materials

Hazardous decomposition

products

May include oxides of silica, aluminium, sodium and potassium.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may

irritate respiratory system.

Skin contact Dust or powder may irritate the skin.

Eye contact Causes eye irritation.

Ingestion Not applicable under normal conditions of use. May cause gastrointestinal irritation if ingested.

Symptoms related to the physical, chemical and toxicological characteristics Causes eye irritation. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the

chest. Shortness of breath.

Information on toxicological effects

Acute toxicity

Test Results Components **Species**

EXPANDED PERLITE (CAS 93763-70-3)

Acute Oral

LD50 Mouse 12960 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Exposure to respirable crystalline silica in the form of guartz or cristobalite from occupational

> sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Test Results Components

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

Aquatic Acute

Fish LC50 Zebra danio (Danio rerio) > 10000 mg/l, 96 Hours OECD SIDS

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, **Disposal instructions**

whether the product meets RCRA criteria for hazardous waste.

Dispose in accordance with all applicable regulations. Local disposal regulations

Material name: FireDefender® Expanded Perlite

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Serious eye damage or eye irritation Classified hazard

categories Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to CRYSTALLINE SILICA (QUARTZ), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA (QUARTZ) (CAS Listed: October 1, 1988

14808-60-7)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

October-16-2015 Issue date **Revision date** November-05-2018

Version #

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer This SDS is intended to guickly provide useful information to the user(s) of this material or product.

It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other

safety and health information about this product is inaccurate or incomplete.

Revision information Regulatory information: California Proposition 65

Regulatory information: US federal regulations