

SAFETY DATA SHEET

1. Identification

Product identifier DENSICAL® HP
Product list DENSICAL® HP BR-775, NV-775
Other means of identification
SDS number GP-42D1
Recommended use Industrial plaster
Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name GP Industrial Plasters LLC
Address 100 Peachtree Street, NW
 Atlanta, GA 30303
Telephone Technical Information 800.225.6119
 (M)SDS Request 404.652.5119
E-mail MSDSREQ@GAPAC.COM
Emergency phone number Chemtrec - Emergency 800.424.9300

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Acute toxicity, oral Category 4
 Eye irritation Category 2A
 Sensitization, skin Category 1
 Carcinogenicity Category 1A
 Specific target organ toxicity, single exposure Category 3 respiratory tract irritation
 Specific target organ toxicity, repeated exposure Category 1 (lung)
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause cancer. Causes damage to organs (lung) through prolonged or repeated exposure.

Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. After mixing with water, do not allow prolonged contact with skin until the product has completely hardened and cooled.

| | |
|--|---|
| Response | If swallowed: Rinse mouth. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention. Specific treatment (see section 4 on the SDS). |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS). Protect from moisture. |
| Disposal | Dispose of contents/container in accordance with applicable regulations. |
| Hazard(s) not otherwise classified (HNOC) | Heat develops as product hardens. May cause serious burns during hardening (rehydration) resulting in possible permanent injury. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| GYPSUM (CALCIUM SULFATE) | | 10101-41-4 | 60 - 80 |
| TALC | | 14807-96-6 | 10 - 30 |
| CRYSTALLINE SILICA (QUARTZ) | | 14808-60-7 | 5 - 10 |
| PORTLAND CEMENT | | 65997-15-1 | 0.5 - 1.5 |
| Other components below reportable levels | | | 0.1 - 1 |

The specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Gypsum (calcium sulfate), talc and Portland Cement contain naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

4. First-aid measures

| | |
|---|---|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. |
| Eye contact | Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell. |
| Most important symptoms/effects, acute and delayed | Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. Prolonged exposure may cause chronic effects. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | None known. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |

| | |
|---|--|
| Fire fighting equipment/instructions | Use water spray to cool unopened containers. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | Sweep up or gather material and place in appropriate container for disposal. Minimize dust generation and accumulation. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Store in a dry place. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep away from food, drink and animal feedingstuffs. |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|------------------------|----------------------|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | PEL | 0.05 mg/m ³ | Respirable dust. |
| GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4) | PEL | 5 mg/m ³ | Respirable fraction. |
| PORTLAND CEMENT (CAS 65997-15-1) | PEL | 15 mg/m ³ | Total dust. |
| | | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value |
|-----------------------|------|----------|
| TALC (CAS 14807-96-6) | TWA | 20 mppcf |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|------|-------------------------|----------------------|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | TWA | 0.025 mg/m ³ | Respirable fraction. |
| GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4) | TWA | 10 mg/m ³ | Inhalable fraction. |
| PORTLAND CEMENT (CAS 65997-15-1) | TWA | 1 mg/m ³ | Respirable fraction. |
| TALC (CAS 14807-96-6) | TWA | 2 mg/m ³ | Respirable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|--|---|----------------------|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | TWA | 0.05 mg/m ³ | Respirable dust. |
| GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4) | TWA | 5 mg/m ³ | Respirable. |
| PORTLAND CEMENT (CAS 65997-15-1) | TWA | 10 mg/m ³ 5 mg/m ³ | Total Respirable. |
| TALC (CAS 14807-96-6) | TWA | 10 mg/m ³ 2 mg/m ³ | Total Respirable. |
| Biological limit values | No biological exposure limits noted for the ingredient(s). | | |
| Exposure guidelines | Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. | | |
| Appropriate engineering controls | When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust. | | |
| Individual protection measures, such as personal protective equipment | | | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Safety shower/eye wash fountain must be readily available in the workplace area (29 CFR 1910.151(c)). | | |
| Skin protection | | | |
| Hand protection | Wear appropriate chemical resistant gloves. | | |
| Other | Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)). | | |
| Respiratory protection | A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2). | | |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. | | |
| General hygiene considerations | Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. | | |

9. Physical and chemical properties

| | |
|---|-----------------------------|
| Appearance | Powder |
| Physical state | Solid. |
| Form | Powder. |
| Color | Light grey to white |
| Odor | Low odor |
| Odor threshold | Not available. |
| pH | 8 - 10 |
| Melting point/freezing point | 2642 °F (1450 °C) estimated |
| Initial boiling point and boiling range | Not applicable |
| Flash point | Not applicable |
| Evaporation rate | Not available |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not applicable |

| | |
|--|-----------------------|
| Flammability limit - upper (%) | Not applicable |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not applicable |
| Vapor density | Not applicable |
| Relative density | 2.6 g/cm ³ |
| Solubility(ies) | |
| Solubility (water) | 0.6 - 0.8 % @ 22°C |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not applicable |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Flash point class | Not flammable |
| Percent volatile | 0 % estimated |
| Specific gravity | 2.6 |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | Reacts with water (normal condition of use). |
| Chemical stability | Stable at normal conditions. |
| Possibility of hazardous reactions | Not expected under normal conditions of use. |
| Conditions to avoid | Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Exposure to moisture. |
| Incompatible materials | Acids. |
| Hazardous decomposition products | May include and are not limited to: calcium oxide and sulfur dioxide. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system. |
| Skin contact | Dust or powder may irritate the skin. May cause an allergic skin reaction. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Harmful if swallowed. |

| | |
|---|---|
| Symptoms related to the physical, chemical and toxicological characteristics | Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. |
|---|---|

Information on toxicological effects

| | |
|-----------------------|-----------------------|
| Acute toxicity | Harmful if swallowed. |
|-----------------------|-----------------------|

| Product | Species | Test Results |
|---------------------|----------------|---------------------|
| DENSCAL® HP | | |
| <u>Acute</u> | | |
| Oral | | |
| ATEmix | | 1438.704 mg/kg |

| Components | Species | Test Results |
|---|---------|--------------|
| GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | > 1581 mg/kg |
| TALC (CAS 14807-96-6) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 920 mg/kg |

* Estimates for product may be based on additional component data not shown.

| | |
|--|---|
| Skin corrosion/irritation | Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. |
| Serious eye damage/eye irritation | Causes serious eye irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | May cause an allergic skin reaction. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure. |

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|--|---|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | 1 Carcinogenic to humans. |
| TALC (CAS 14807-96-6) | 2B Possibly carcinogenic to humans. |
| | 3 Not classifiable as to carcinogenicity to humans. |

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

| | |
|--|--------|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | Cancer |
|--|--------|

US. National Toxicology Program (NTP) Report on Carcinogens

| | |
|--|-------------------------------|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | Known To Be Human Carcinogen. |
|--|-------------------------------|

| | |
|---|--|
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure | Causes damage to organs (lung) through prolonged or repeated exposure. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|--|--------------------------------|----------------------------------|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Fish | LC50 Zebra danio (Danio rerio) | > 10000 mg/l, 96 Hours OECD SIDS |
| GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4) | | |
| Aquatic | | |
| Fish | LC50 Fish | 2980 mg/l, 96 Hours |

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential**Mobility in soil** No data available.**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.**13. Disposal considerations****Disposal instructions** Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.**Local disposal regulations** Dispose in accordance with all applicable regulations.**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. Transport information****DOT**

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.**15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

| | |
|--|---|
| CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) | Cancer lung effects immune system effects kidney effects |
|--|---|

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

| | |
|-------------------------------------|--|
| Classified hazard categories | Acute toxicity (any route of exposure) Serious eye damage or eye irritation Respiratory or skin sensitization Carcinogenicity Specific target organ toxicity (single or repeated exposure) |
|-------------------------------------|--|

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including CRYSTALLINE SILICA (QUARTZ), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)
TALC (CAS 14807-96-6)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|---------------|---|
| Issue date | March-04-2015 |
| Revision date | August-20-2018 |
| Version # | 05 |
| HMIS® ratings | Health: 2* Flammability: 0 Physical hazard: 1 |
| NFPA ratings | Health: 2 Flammability: 0 Instability: 0 |

Disclaimer

This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

Revision information

Identification: Recommended restrictions
Toxicological Information: Toxicological Data
Regulatory information: California Proposition 65
Regulatory information: US federal regulations