

# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Glass Mat Faced Gypsum Panels</b>
<b>Product list</b>	Product List A DensArmor Plus® Interior Panel DensArmor Plus® Fireguard® Abuse-Resistant Panels DensArmor Plus® Fireguard® Impact-Resistant Panels DensArmor Plus® Fireguard® Interior Panels DensDeck® Prime Roof Board DensDeck® Roof Board DensDeck® Prime Fireguard® Roof Board DensDeck® Fireguard® Roof Board DensElement™ Sheathing DensGlass® Fireguard® Sheathing DensGlass® Shaftliner DensGlass® Sheathing DensShield® Fireguard® Tile Backer DensShield® Tile Backer ..... Product List B DensArmor Plus® Fireguard C® Interior Panels .....
<b>Other means of identification</b>	
<b>Product code</b>	GP-71C
<b>Recommended use</b>	Products accommodate a wide range of wall, floor, ceiling and roof applications.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer</b>	
<b>Company name</b>	Georgia-Pacific Gypsum LLC
<b>Address</b>	133 Peachtree Street, NE Atlanta, GA 30303
<b>Telephone</b>	Technical Information: 800.225.6119 (M)SDS Request: 404.652.5119
<b>E-mail</b>	MSDSREQ@GAPAC.COM
<b>Emergency phone number</b>	Chemtrec - Emergency: 800.424.9300
<b>Importer/Supplier/Distributor</b>	
<b>Company name</b>	Georgia-Pacific Canada LP
<b>Address</b>	350 Argyle Street North Caledonia, ON N3W 1M2
<b>Telephone</b>	Technical Information: 800.225.6119 (M)SDS Request: 404.652.5119
<b>E-mail</b>	MSDSREQ@GAPAC.com
<b>Emergency phone number</b>	Chemtrec - Emergency: 800.424.9300

## 2. Hazard identification

<b>Emergency overview</b>	This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities such as cutting, sanding, or otherwise working with this product that generate large amount of dusts. Those hazards associated with large amount of dusts are described below.	
<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Eye irritation	Category 2B

<b>Environmental hazards</b>	Not classified.
<b>Label elements</b>	
<b>Hazard symbol</b>	None.
<b>Signal word</b>	Warning
<b>Hazard statement</b>	Causes eye irritation.
<b>Precautionary statement</b>	
<b>Prevention</b>	Wash thoroughly after handling. Observe good industrial hygiene practices.
<b>Response</b>	Wash hands after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Storage</b>	Store away from acids.
<b>Disposal</b>	Dispose of contents/container in accordance with applicable regulations.
<b>Other hazards</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

<b>Chemical name</b>	<b>Common name and synonyms</b>	<b>CAS number</b>	<b>%</b>
Calcium Sulfate Dihydrate		10101-41-4	80 - 100
VERMICULITE**		1318-00-9	0 - 10
FIBROUS GLASS		65997-17-3	1 - 5
CRYSTALLINE SILICA (QUARTZ)*		14808-60-7	0.1 - 1

**Composition comments**      \*\* Found in products in List B, Section 1 of this SDS.

Gypsum (calcium sulfate, dihydrate) and vermiculite contain naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

\*The weight percent for crystalline silica represents total crystalline silica and not the respirable fraction. Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

### 4. First-aid measures

<b>Inhalation</b>	If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Remove and isolate contaminated clothing and shoes. For skin contact, wash immediately with soap and water. Get medical attention if symptoms occur. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.
<b>Eye contact</b>	Do not rub the eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth. May result in obstruction and irritation if ingested. Get medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.

<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Firefighters should wear full protective clothing including self contained breathing apparatus.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Avoid inhalation of dust from the spilled material. In the case of dust or aerosol formation use respirator with an approved filter. Use personal protection recommended in Section 8. Keep unnecessary personnel away.
<b>Methods and materials for containment and cleaning up</b>	Minimize dust generation. Sweep up or gather material and place in an appropriate container for disposal. Utilize wet methods, if appropriate, to minimize dust. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Keep out of drains, sewers, ditches, and waterways.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Provide appropriate exhaust ventilation at places where dust is formed. Minimise dust generation and accumulation. Do not breathe dust. Do not get this material in contact with eyes. Do not taste or swallow. Avoid prolonged exposure. Observe good industrial hygiene practices. Use only in well-ventilated areas. Do not eat or drink while using the product. Wash hands before eating, drinking or smoking.
<b>Conditions for safe storage, including any incompatibilities</b>	Store level and keep dry. Dewpoint or other conditions causing the presence of moisture can damage the product during storage. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### ACGIH

Components	Type	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm <sup>3</sup>	Fiber.

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	TWA	10 mg/m <sup>3</sup>	
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable particles.
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm <sup>3</sup>	Fiber.
		5 mg/m <sup>3</sup>	Fiber, total
		5 mg/m <sup>3</sup>	Total particulate.
VERMICULITE** (CAS 1318-00-9)	TWA	3 mg/m <sup>3</sup>	Respirable particles.
		10 mg/m <sup>3</sup>	Total particulate.

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	STEL	20 mg/m <sup>3</sup>	Total dust.
	TWA	10 mg/m <sup>3</sup>	Inhalable
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm <sup>3</sup>	Fiber.
		5 mg/m <sup>3</sup>	Inhalable fibers.
VERMICULITE** (CAS 1318-00-9)	TWA	3 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Total dust.

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm <sup>3</sup>	Fiber.
		5 mg/m <sup>3</sup>	Inhalable fraction.

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable fraction.
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.5 fibers/cc	Respirable fibers.
		5 mg/m <sup>3</sup>	Inhalable fraction.
VERMICULITE** (CAS 1318-00-9)	TWA	3 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Inhalable fraction.

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	TWA	5 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total dust.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable dust.
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm <sup>3</sup>	Fiber.
		10 mg/m <sup>3</sup>	fibers, total dust
VERMICULITE** (CAS 1318-00-9)	TWA	10 mg/m <sup>3</sup>	Total dust.

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

Components	Type	Value	Form
Calcium Sulfate Dihydrate (CAS 10101-41-4)	15 minute	20 mg/m <sup>3</sup>	

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
	8 hour	10 mg/m <sup>3</sup>	
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	8 hour	0.05 mg/m <sup>3</sup>	Respirable fraction.
FIBROUS GLASS (CAS 65997-17-3)	15 minute	10 mg/m <sup>3</sup>	Inhalable fraction.
	8 hour	0.2 fibers/cc	Respirable fibers.
		5 mg/m <sup>3</sup>	Inhalable fraction.
VERMICULITE** (CAS 1318-00-9)	15 minute	6 mg/m <sup>3</sup>	Respirable fraction.
		20 mg/m <sup>3</sup>	Inhalable fraction.
	8 hour	3 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Inhalable fraction.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

\*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

**Appropriate engineering controls**

Score and snap method recommended. When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL (occupational exposure limit), suitable respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Safety glasses or goggles are recommended when using this product. Eye wash fountain is recommended.

**Skin protection**

**Hand protection**

For prolonged or repeated skin contact use suitable protective gloves.

**Other**

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Safety shower/eye wash fountain is recommended in the workplace area.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal hazards**

Not applicable.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Keep away from food and drink.

**9. Physical and chemical properties**

**Appearance**

Gypsum boards

**Physical state**

Solid.

**Form**

Solid

**Colour**

Facing color varies

**Odour**

Low odor

**Odour threshold**

Not available.

**pH**

6 - 8

**Melting point/freezing point**

Not applicable.

**Initial boiling point and boiling range**

Not applicable.

**Flash point**

Not applicable.

<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not applicable.
<b>Flammability limit - upper (%)</b>	Not applicable.
<b>Explosive limit - lower (%)</b>	Not applicable.
<b>Explosive limit - upper (%)</b>	Not applicable.
<b>Vapour pressure</b>	Not applicable.
<b>Vapour density</b>	Not applicable.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	0.2 % @ 22°C
<b>Partition coefficient (n-octanol/water)</b>	Not applicable.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not applicable.
<b>Other information</b>	
<b>Flash point class</b>	Not flammable
<b>Specific gravity</b>	2.2 - 2.4

## 10. Stability and reactivity

<b>Reactivity</b>	Contact with strong acids produces carbon dioxide.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
<b>Incompatible materials</b>	Strong acids.
<b>Hazardous decomposition products</b>	May include and are not limited to: calcium oxide and sulfur dioxide.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Inhalation of dusts may cause respiratory irritation.
<b>Skin contact</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	Dust in the eyes will cause irritation.
<b>Ingestion</b>	Not applicable under normal conditions of use. May cause gastrointestinal irritation if ingested.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Direct contact with eyes may cause temporary irritation.
---	---

### Information on toxicological effects

#### Acute toxicity

Product	Species	Test Results
Glass Mat Faced Gypsum Panels		
<u>Acute</u>		
<b>Oral</b>		
ATEmix		1728 mg/kg

Components	Species	Test Results
Calcium Sulfate Dihydrate (CAS 10101-41-4)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 1581 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Dust in the eyes will cause irritation.	
<b>Respiratory or skin sensitisation</b>		
<b>Canada - Alberta OELs: Irritant</b>		
FIBROUS GLASS (CAS 65997-17-3)	Irritant	
<b>Respiratory sensitisation</b>	Not likely to cause respiratory sensitization.	
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.	
<b>Germ cell mutagenicity</b>	Not classified.	
<b>Carcinogenicity</b>	Not expected to be hazardous by OSHA/WHMIS criteria.	
<p>Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.</p>		
<b>ACGIH Carcinogens</b>		
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	A2 Suspected human carcinogen.	
FIBROUS GLASS (CAS 65997-17-3)	A2 Suspected human carcinogen. A3 Confirmed animal carcinogen with unknown relevance to humans. A4 Not classifiable as a human carcinogen.	
<b>Canada - Alberta OELs: Carcinogen category</b>		
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	Suspected human carcinogen.	
FIBROUS GLASS (CAS 65997-17-3)	Suspected human carcinogen.	
<b>Canada - Manitoba OELs: carcinogenicity</b>		
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	Suspected human carcinogen.	
FIBROUS GLASS (CAS 65997-17-3)	Confirmed animal carcinogen with unknown relevance to humans. Not classifiable as a human carcinogen. Suspected human carcinogen.	
<b>Canada - Quebec OELs: Carcinogen category</b>		
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	Suspected carcinogenic effect in humans.	
FIBROUS GLASS (CAS 65997-17-3)	Detected carcinogenic effect in animals.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	1 Carcinogenic to humans.	
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>		
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	Known To Be Human Carcinogen.	
<b>Reproductive toxicity</b>	Not classified.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	Not classified.	
<b>Chronic effects</b>	Not hazardous under normal conditions of use.	
<b>Further information</b>	*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.	

## 12. Ecological information

<b>Ecotoxicity</b>	Contains a substance which causes risk of hazardous effects to the environment. Not considered to be harmful to aquatic life.
--------------------	---

Components	Species	Test Results
------------	---------	--------------

Calcium Sulfate Dihydrate (CAS 10101-41-4)

**Aquatic**

*Acute*

Fish LC50 Fathead minnow (*Pimephales promelas*) > 1970 mg/l, 96 hours

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)

**Aquatic**

*Acute*

Fish LC50 Zebra danio (*Danio rerio*) > 10000 mg/l, 96 Hours OECD SIDS

FIBROUS GLASS (CAS 65997-17-3)

**Aquatic**

*Acute*

Fish LC50 Fish > 1000 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations.

**Contaminated packaging** Not available.

### 14. Transport information

**TDG**

Not regulated as dangerous goods.

**IATA**

Not regulated as dangerous goods.

**IMDG**

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

### 15. Regulatory information

**Canadian regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Controlled Drugs and Substances Act**

Not regulated.

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Not regulated.

**International regulations**

**Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.



**Kyoto Protocol**

Not applicable.

**Montreal Protocol**

Not applicable.

**Basel Convention**

Calcium Sulfate Dihydrate (CAS 10101-41-4)

FIBROUS GLASS (CAS 65997-17-3)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information****Issue date** 03-24-2017**Revision date** 07-25-2019**Version No.** 02**Further information** HMIS® is a registered trade and service mark of the NPCA.

**Disclaimer** This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

**Revision information** Composition / Information on Ingredients: Ingredients  
 Accidental release measures: Methods and materials for containment and cleaning up  
 Handling and storage: Conditions for safe storage, including any incompatibilities