

SAFETY DATA SHEET

1. Identification

Product identifier
Product list
WOOD PRODUCTS (PMDI BONDED)

Temstock Free, Temstock Free MR, Temstock MR,

UltraStock MDF produced with pMDI resin Shelving, UltraStock Free, UltraStock Free MR, Ultrastock HD

DryGuard® OSB Sturd-I-Floor, DryMax®, Web stock, FiberStrong® Rim Board

FiberStrong HD™ (Mill#s 531, 532, 530, 475),
Blue Ribbon® (Mill#s 531, 532, 530, 475),
Camouflage Panel Featuring Mossy Oak® (Mill#s 531, 475),
Realtree Camouflage Panel® (Mill#s 531, 475),
Thermostat® OSB Radiant Barrier Roof Sheathing (Mill# 531, 475),
ForceField™ air and water barrier panels (Mill#s 475, 500, 531)
----- X-----
----- X-----

® is a Registered Trademark owned by or licensed to Georgia-Pacific Wood Products LLC
™ is a Trademark owned by or licensed to Georgia-Pacific Wood Products LLC

Other means of identification
SDS number

GP-34B

Recommended use

Building Materials - Decorative

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information
Manufacturer
Company name

Georgia-Pacific Wood Products LLC

Address

133 Peachtree Street, NE
Atlanta, GA 30303

Telephone

Technical Information: 800.284.5347
(M)SDS Request: 404.652.5119

e-mail

MSDSREQ@GAPAC.COM

Emergency phone number

Chemtrec - Emergency: 800.424.9300

Importer/Supplier/Distributor
Company name

GP North Woods LP

Address

327022 Highway 11
Englehart, ON P0J 1H0

Telephone

Technical Information: 705-544-2395
(M)SDS Request: 404.652.5119

e-mail

MSDSREQ@GAPAC.com

Emergency phone number

Chemtrec - Emergency: 800.424.9300

2. Hazard(s) identification

Emergency overview

This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities (e.g., grinding, sanding, cutting, pulverizing) that reduce its particle size. Those hazards are described below.

Physical hazards

Combustible dusts Category 1

Health hazards

Eye irritation Category 2B

Sensitization, respiratory	Category 1
Sensitization, skin	Category 1A
Carcinogenicity	Category 1A
Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation
Specific target organ toxicity following repeated exposure	Category 1 (respiratory system)
Environmental hazards	Not classified.

Label elements



Signal word

Danger

Hazard statement

May cause an allergic skin reaction. Causes eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause cancer. Causes damage to organs (respiratory system) through prolonged or repeated exposure. If small particles of wood dust are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Prevent dust accumulation and airborne dispersion of dust to minimize flash fire and explosion hazard. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
WOOD/WOOD DUST		Not assigned	87 - < 92
4,4'-DIPHENYLMETHANE DIISOCYANATE		101-68-8	0.5 - < 4
POLYMERIC MDI (pMDI)		9016-87-9	1 - 5
2,4'-DIPHENYL METHANE DIISOCYANATE		5873-54-1	< 0.4
Other components below reportable levels			< 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove from area of exposure. If the affected person is not breathing, apply artificial respiration. If persistent irritation, severe coughing or breathing difficulty occurs, seek medical attention.

Skin contact	If irritation develops, wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Get medical attention if irritation develops and persists.
Ingestion	If wood or wood dust is swallowed, get immediate medical attention or advice -- Do not induce vomiting.
Most important symptoms/effects, acute and delayed	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause an allergic skin reaction. Dermatitis. Rash. May cause respiratory irritation. Difficulty in breathing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). Apply extinguishing media carefully to avoid creating airborne dust. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Unsuitable extinguishing media	Heavy water (or jet) stream may cause dust to become airborne and create a flash fire hazard or an explosive atmosphere.
Specific hazards arising from the chemical	Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	To avoid dust clouds, responders should use the extinguisher from as far away as possible and apply the extinguishing agent as gently as possible. The main considerations with hose stream operation are to avoid creating combustible dust clouds or introducing more air. In particular, the use of solid streams and direct dust pile hits can disperse dust into the air creating a potential flash fire hazard. The best way to apply water is in a medium to wide-pattern, as gently as possible. Responders should use a low nozzle pressure and loft the stream onto the burning material from as far away as the stream will reach.
General fire hazards	May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Vacuum dust with dust ignition proof vacuum or wet sweep small wood pieces and dust; place in appropriate container for disposal. Gather larger pieces by an appropriate method. Reduce airborne dust by use of wet methods (e.g. water mist) and prevent scattering by moistening with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Dust can form an explosive mixture in air. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Minimise dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. If flash fire or explosion hazard is present, wear flame resistant clothing and face/head protection. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Use personal protective equipment as required. Ensure dust collection systems used for conveying combustible wood dusts are protected with and equipped with fire and explosion prevention and protection equipment. See NFPA 664 and NFPA 69 for further requirements, information and guidance.

Conditions for safe storage, including any incompatibilities

Store flat, supported and protected from direct contact with the ground. Store away from incompatible materials (see Section 10 of the SDS). Store in a cool dry place.

8. Exposure controls/personal protection

Occupational exposure limits

ACGIH

Components	Type	Value	Form
WOOD/WOOD DUST	TWA	1 mg/m ³	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.005 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.05 mg/m ³	
POLYMERIC MDI (pMDI) (CAS 9016-87-9)	TWA	0.005 ppm 0.07 mg/m ³	
WOOD/WOOD DUST	TWA	0.005 ppm 3 mg/m ³ 10 mg/m ³	Respirable particles. Total particulate.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	Ceiling	0.01 ppm	
WOOD/WOOD DUST	TWA	0.005 ppm 3 mg/m ³ 10 mg/m ³	Respirable fraction. Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.005 ppm	

Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	Ceiling	0.02 ppm	

Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
WOOD/WOOD DUST	TWA	0.005 ppm	
	STEL	10 mg/m ³	Dust.
	TWA	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.051 mg/m ³	
WOOD/WOOD DUST	TWA	0.005 ppm	
		10 mg/m ³	Total dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Canada - British Columbia OELs: Skin designation**

4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8) Can be absorbed through the skin.

Appropriate engineering controls Due to the fire and explosive potential of dust when suspended in air, precautions should be taken when material is used in any operation which may generate dust. Local exhaust, general dilution ventilation in enclosed areas, and explosion proof equipment is recommended. Use wet methods, if appropriate, to reduce airborne dust concentrations.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses or goggles are recommended when using this product.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Safety shower/eye wash fountain is recommended in the workplace area.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using, do not eat, drink or smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Rigid boards or panels

Physical state Solid.

Form Solid wood

Colour Various

Odour Not available.

Odour threshold Not available.

pH Not applicable

Melting point/freezing point Not applicable

Initial boiling point and boiling range Not available.

Flash point Not applicable

Evaporation rate Not applicable

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 40 g/cm³ for wood dust (Note: The LEL is equivalent to the Minimum Explosive Concentration (MEC) for the combustible dust. The MEC will vary with particle size of the wood dust. Recommend MEC testing for specific wood dust particle sizes generated or handled.)

Flammability limit - upper (%)	Not available
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	Not applicable
Vapour density	Not applicable
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not applicable
Auto-ignition temperature	204.4 - 260 °C (399.92 - 500 °F) for wood
Decomposition temperature	Not available
Viscosity	Not available.
Other information	
Bulk density	Not applicable
Dust explosion properties	
St class	1 Weak explosion.
Explosive properties	Not explosive.
Flash point class	Combustible
Oxidising properties	Not oxidising.
Specific gravity	Variable

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Dust accumulation, dispersion of dust in air, high temperatures, open flame, sparks, or other sources of ignition.
Incompatible materials	Strong acids, alkalis, oxidizing agents and drying oils.
Hazardous decomposition products	Thermal decomposition may emit irritating fumes or gases of carbon monoxide, carbon dioxide, aldehydes, or organic acids.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes eye irritation.
Ingestion	Not applicable under normal conditions of use. May result in obstruction or temporary irritation of the digestive tract.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Dusts may irritate the respiratory tract, skin and eyes. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test results
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg
Inhalation		
<i>Vapour</i>		
LC50		0.178 mg/l
Oral		
LD50	Rat	> 10000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitisation

Canada - British Columbia OELs: Respiratory or skin sensitiser

4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8) Capable of causing respiratory, dermal or conjunctival sensitization.

Canada - Quebec OELs: Sensitizer

4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8) Sensitiser.

Canada - Saskatchewan OELs Hazard Data: Sensitiser

WOOD/WOOD DUST (CAS Not assigned) Sensitiser.

Respiratory sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Wood dust generated from sawing, sanding or machining this product may cause nasal dryness, irritation, coughing and sinusitis. The International Agency for Research on Cancer (IARC), and National Toxicology Program (NTP) classifies wood dust as a carcinogen. This classification is based on the increased occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation noted insufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon, or rectum with exposure to wood dust.

IARC Monographs. Overall Evaluation of Carcinogenicity

4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8) 3 Not classifiable as to carcinogenicity to humans.

POLYMERIC MDI (pMDI) (CAS 9016-87-9) 3 Not classifiable as to carcinogenicity to humans.

WOOD/WOOD DUST (CAS Not assigned) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

WOOD/WOOD DUST (CAS Not assigned) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure Causes damage to organs (respiratory system) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Empty packaging/container can be disposed in accordance with all applicable regulations.

14. Transport information**TDG**

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information**Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	05-31-2017
Version No.	01

Disclaimer

This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

Revision information

Product and Company Identification: Synonyms
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Regulatory Information: United States
HazReg Data: North America
GHS: Classification

WOOD PRODUCTS (PMDI BONDED)

EN

Danger

Hazard statement

May cause an allergic skin reaction. Causes eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause cancer. Causes damage to organs (respiratory system) through prolonged or repeated exposure. If small particles of wood dust are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Prevent dust accumulation and airborne dispersion of dust to minimize flash fire and explosion hazard. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. IF skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Dispose of contents/container in accordance with local/regional/national/international regulations.

FR-CA

Danger

Mention de danger

Peut provoquer une allergie cutanée. Provoque une irritation des yeux. Peut provoquer des symptômes allergiques ou d'asthme ou des difficultés respiratoires par inhalation. Peut irriter les voies respiratoires. Peut provoquer le cancer. Risque avéré d'effets graves pour les organes (respiratory system) à la suite d'expositions répétées ou d'une exposition prolongée. Si des petites particules de poussière de bois sont émises par des activités de transformation, de manipulation ou par d'autres moyens, elles peuvent former des concentrations de poussières combustibles dans l'air.

Conseil de prudence

Se procurer les instructions avant utilisation. Ne pas manipuler avant d'avoir lu et compris toutes les précautions de sécurité. Porter des gants/vêtements de protection/équipement de protection des yeux/du visage. Porter une protection respiratoire. Ne pas respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols. Se laver soigneusement après manipulation. Ne pas manger, boire ou fumer en manipulant ce produit. Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail. Utiliser seulement en plein air ou dans un endroit bien ventilé. Éviter l'empoussièrement et la dispersion des particules de poussière dans l'air afin de minimiser les risques d'inflammation instantanée et d'explosion. Tenir à l'écart de la chaleur, des surfaces chaudes, des étincelles, des flammes nues et de toute autre source d'ignition. Ne pas fumer. EN CAS DE CONTACT AVEC LES YEUX: Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. Si l'irritation des yeux persiste : Demander un avis médical/Consulter un médecin. EN CAS DE CONTACT AVEC LA PEAU: Laver abondamment à l'eau. En cas d'irritation ou d'éruption cutanée : Obtenir une consultation médicale ou des soins médicaux. Enlever les vêtements contaminés et les laver avant réutilisation. EN CAS D'INHALATION: Transporter la personne à l'extérieur et la maintenir dans une position où elle peut confortablement respirer. En cas de symptômes respiratoires: Appeler un CENTRE ANTIPOISON/un médecin. EN CAS d'exposition prouvée ou suspectée : Demander un avis médical/Consulter un médecin. En cas d'incendie : utiliser un agent d'extinction approprié. Stocker dans un endroit bien ventilé. Conserver à l'écart de matières incompatibles (voir rubrique 10). Eliminer le contenu/réceptier conformément à la réglementation locale/régionale/nationale/internationale.



Product list / Liste de produits:

Temstock Free, Temstock Free MR, Temstock MR,
UltraStock MDF produced with pMDI resin Shelving, UltraStock Free, UltraStock Free MR, UltraStock HD
DryGuard® OSB Sturd-I-Floor, DryMax®, Web stock, FiberStrong® Rim Board
FiberStrong HD™ (Mill#s 531, 532, 530, 475), Blue Ribbon® (Mill#s 531, 532, 530, 475), Camouflage Panel Featuring Mossy
Oak® (Mill#s 531, 475),
Realtree Camouflage Panel® (Mill#s 531, 475), Thermostat® OSB Radiant Barrier Roof Sheathing (Mill# 531, 475),
ForceField™ air and water barrier panels (Mill#s 475, 500, 531)

Manufacturer:
Company name: Georgia-Pacific Wood Products LLC
Address: 3300 Commerce Street, NE
Atlanta, GA 30326
Telephone: Technical Information: 800-284-5347
(MSDS Request: 404-652-5119)
e-mail: MSDSREQ@GAPAC.COM
Emergency phone number: Chemtrec - Emergency:
800-461-9300



Importer/Supplier/Distributor:
Company name: GP North Woods LP
Address: 37022 Highway 11
Lafayette, LA 70508
Telephone: Technical Information: 705-544-2995
(MSDS Request: 404-652-5119)
e-mail: MSDSREQ@GAPAC.COM
Emergency phone number: Chemtrec - Emergency: