

## 1. Identification

<b>Product identifier</b>	<b>Certrock</b>
<b>Product list</b>	Certrock BR-312
<b>Other means of identification</b>	
<b>SDS number</b>	GP-56
<b>Recommended use</b>	Industrial plaster
<b>Recommended restrictions</b>	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

<b>Company name</b>	GP Industrial Plasters LLC
<b>Address</b>	100 Peachtree Street, NW Atlanta, GA 30303
<b>Telephone</b>	Technical Information: 800.225.6119 (M)SDS Request: 404.652.5119
<b>e-mail</b>	MSDSREQ@GAPAC.COM
<b>Emergency phone number</b>	Chemtrec - Emergency: 800.424.9300

<b>Importer/Supplier/Distributor</b>	Not applicable.
--------------------------------------	-----------------

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Serious eye damage	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1A
	Specific target organ toxicity following repeated exposure	Category 1 (lung)
	Health hazards not otherwise classified	Category 1
<b>Environmental hazards</b>	Not classified.	

#### Label elements



**Signal word** Danger

**Hazard statement** Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer. Causes damage to organs (lung) through prolonged or repeated exposure. Heat develops as product hardens. May cause serious burns during hardening (rehydration) resulting in possible permanent injury.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. After mixing with water, do not allow prolonged contact with skin until the product has completely hardened and cooled.

### Response

If swallowed: Rinse mouth. Call a poison center/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see section 4 on the SDS).

### Storage

Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS). Protect from moisture.

### Disposal

Dispose of contents/container in accordance with applicable regulations.

### Other hazards

None known.

### Supplemental information

None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Calcium sulfate hemihydrate		10034-76-1	80 - 90
Portland Cement		65997-15-1	5 - 10
CRYSTALLINE SILICA (QUARTZ)*		14808-60-7	1 - 3
FORMALDEHYDE-NAPHTHALENESU LFONIC ACID POLYMER SODIUM SALT		9084-06-4	1 - 3
Other components below reportable levels			1 - 3

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### Composition comments

Gypsum (calcium sulfate) and Portland Cement contain naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

## 4. First-aid measures

### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

### Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

### Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

### Most important symptoms/effects, acute and delayed

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

### General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Use water spray to cool unopened containers.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Sweep up or gather material and place in appropriate container for disposal. Minimise dust generation and accumulation. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground. If large quantities enter a waterway, advise local authorities.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store in original tightly closed container. Store in a dry place. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m<sup>3</sup>, non-standard units

Components	Type	Value	Form
Calcium sulfate hemihydrate (CAS 10034-76-1)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable particles.
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m <sup>3</sup>	

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value	Form
Calcium sulfate hemihydrate (CAS 10034-76-1)	STEL	20 mg/m <sup>3</sup>	Total dust.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	3 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Total dust.

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
Calcium sulfate hemihydrate (CAS 10034-76-1)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.

**Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
Calcium sulfate hemihydrate (CAS 10034-76-1)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.

**Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable dust.
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total dust.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

**Appropriate engineering controls**

When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles). Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Safety shower/eye wash fountain must be readily available in the workplace area (29 CFR 1910.151(c)).

**Skin protection**

**Hand protection**

Wear appropriate chemical resistant gloves.

**Other**

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Safety shower/eye wash fountain is recommended in the workplace area.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

<b>Physical state</b>	Solid.
<b>Form</b>	Powder.
<b>Colour</b>	Light grey to white

**Odour** Low odor

**Odour threshold** Not available.

**pH** 8 - 10

**Melting point/freezing point** 1450 °C (2642 °F) estimated

**Initial boiling point and boiling range** Not applicable

**Flash point** Not applicable

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not applicable

**Flammability limit - upper (%)** Not applicable

**Explosive limit - lower (%)** Not available.

**Explosive limit – upper (%)** Not available.

**Vapour pressure** Not applicable

**Vapour density** Not applicable

**Relative density** 2.2 g/cm<sup>3</sup>

**Solubility(ies)**

**Solubility (water)** 0.2 % @ 22°C

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** Not applicable

**Decomposition temperature** Not available.

**Viscosity** Not available.

**Other information**

**Density** 2.97 g/cm<sup>3</sup> estimated

**Flash point class** Not flammable

**Specific gravity** 2.2

**10. Stability and reactivity**

**Reactivity** Reacts with water (normal condition of use).

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** Not expected under normal conditions of use.

**Conditions to avoid** Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Exposure to moisture.

**Incompatible materials** Acids.

**Hazardous decomposition products** May include, and are not limited to: calcium oxide and sulfur dioxide.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system.
<b>Skin contact</b>	Dust or powder may irritate the skin. May cause an allergic skin reaction. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
<b>Eye contact</b>	Causes serious eye damage.
<b>Ingestion</b>	Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

### Information on toxicological effects

**Acute toxicity** Harmful if swallowed.

<b>Product</b>	<b>Species</b>	<b>Test results</b>
Cerrock		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	686 mg/l, 4 hours estimated
<b>Oral</b>		
LD50	Rat	1721 mg/kg estimated
<b>Components</b>	<b>Species</b>	<b>Test results</b>
Calcium sulfate hemihydrate (CAS 10034-76-1)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 1581 mg/kg
FORMALDEHYDE-NAPHTHALENESULFONIC ACID POLYMER SODIUM SALT (CAS 9084-06-4)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 5200 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
<b>Serious eye damage/eye irritation</b>	Causes serious eye damage.
<b>Respiratory or skin sensitisation</b>	
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.
<b>Skin sensitisation</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure

## ACGIH Carcinogens

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)  
Portland Cement (CAS 65997-15-1)

A2 Suspected human carcinogen.  
A4 Not classifiable as a human carcinogen.

## Canada - Alberta OELs: Carcinogen category

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)

Suspected human carcinogen.

## Canada - Manitoba OELs: carcinogenicity

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)  
Portland Cement (CAS 65997-15-1)

Suspected human carcinogen.  
Not classifiable as a human carcinogen.

## Canada - Quebec OELs: Carcinogen category

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)

Suspected carcinogenic effect in humans.

## IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)

1 Carcinogenic to humans.

## US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)

Known To Be Human Carcinogen.

### Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

### Specific target organ toxicity - single exposure

Not classified.

### Specific target organ toxicity - repeated exposure

Causes damage to organs (lung) through prolonged or repeated exposure.

### Aspiration hazard

Not an aspiration hazard.

### Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

### Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test results
Calcium sulfate hemihydrate (CAS 10034-76-1)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) > 1970 mg/l, 96 hours
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Zebra danio ( <i>Danio rerio</i> ) > 10000 mg/l, 96 Hours OECD SIDS

### Persistence and degradability

No data is available on the degradability of this product.

### Bioaccumulative potential

### Mobility in soil

No data available.

### Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

### Disposal instructions

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Local disposal regulations

Dispose in accordance with all applicable regulations.

### Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

### Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

### Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### TDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## 15. Regulatory information

### Canadian regulations

#### Controlled Drugs and Substances Act

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

Not applicable.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Calcium sulfate hemihydrate (CAS 10034-76-1)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

**Issue date** 03-01-2017

**Revision date** 11-02-2017

**Version No.** 02

### Disclaimer

This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

### Revision information

Product and Company Identification: Product and Company Identification

Hazard(s) identification: Response

Accidental release measures: Methods and materials for containment and cleaning up

Handling and storage: Conditions for safe storage, including any incompatibilities