

# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Pacific Stone</b>	
<b>Product list</b>	Pacific Stone™ BR-267, NV-267	
<b>Other means of identification</b>		
<b>SDS number</b>	GP-57	
<b>Recommended use</b>	Industrial plaster	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Company name</b>	GP Industrial Plasters LLC	
<b>Address</b>	100 Peachtree Street, NW Atlanta, GA 30303	
<b>Telephone</b>	Technical Information	800.225.6119
	(M)SDS Request	404.652.5119
<b>E-mail</b>	MSDSREQ@GAPAC.COM	
<b>Emergency phone number</b>	Chemtrec - Emergency	800.424.9300

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Skin irritation	Category 2
	Serious eye damage	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1A
	Specific target organ toxicity, repeated exposure	Category 1 (lung)
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer. Causes damage to organs (lung) through prolonged or repeated exposure.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. After mixing with water, do not allow prolonged contact with skin until the product has completely hardened and cooled.
<b>Response</b>	If swallowed: Rinse mouth. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Specific treatment (see section 4 on the SDS).
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS). Protect from moisture.
<b>Disposal</b>	Dispose of contents/container in accordance with applicable regulations.

<b>Hazard(s) not otherwise classified (HNOC)</b>	Heat develops as product hardens. May cause serious burns during hardening (rehydration) resulting in possible permanent injury.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
PORTLAND CEMENT		65997-15-1	45 - 70
GYPSUM (CALCIUM SULFATE)		7778-18-9	15 - 40
KAOLIN†		92704-41-1	3 - 7
CRYSTALLINE SILICA (QUARTZ)		14808-60-7	1 - 5
IRON OXIDE		1309-37-1	1 - 5
FORMALDEHYDE-NAPHTHALENE SULFONIC ACID POLYMER SODIUM SALT		9084-06-4	0.5 - 1.5
TITANIUM DIOXIDE‡		13463-67-7	0.1 - 1
Other components below reportable levels			1 - 5

The specific chemical identity and/or percentage of composition has been withheld as a trade secret.

<b>Composition comments</b>	† Not found in Pacific Stone™ NV-267 formulation. ‡ Contained only in Pacific Stone™ BR-267 formulations.
-----------------------------	--

Gypsum (calcium sulfate), limestone (calcium carbonate), Portland Cement and kaolin contain naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. This product also contains titanium dioxide, which is listed as a possible lung carcinogen. See Section 8 for exposure information.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions**

Move containers from fire area if you can do so without risk.

**Specific methods**

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**

No unusual fire or explosion hazards noted.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up**

Sweep up or gather material and place in appropriate container for disposal. Minimize dust generation and accumulation. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

**Environmental precautions**

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. If large quantities enter a waterway, advise local authorities.

**7. Handling and storage****Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Store in a dry place. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep away from food, drink and animal feedingstuffs.

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	PEL	0.05 mg/m <sup>3</sup>	Respirable dust.
GYPHUM (CALCIUM SULFATE) (CAS 7778-18-9)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
IRON OXIDE (CAS 1309-37-1)	PEL	15 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Total dust. Fume.
KAOLIN† (CAS 92704-41-1)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
PORTLAND CEMENT (CAS 65997-15-1)	PEL	15 mg/m <sup>3</sup> 5 mg/m <sup>3</sup>	Total dust. Respirable fraction.
TITANIUM DIOXIDE‡ (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup> 15 mg/m <sup>3</sup>	Total dust. Total dust.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
GYPHUM (CALCIUM SULFATE) (CAS 7778-18-9)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
KAOLIN† (CAS 92704-41-1)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
PORTLAND CEMENT (CAS 65997-15-1)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.
TITANIUM DIOXIDE‡ (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>	Respirable dust.
GYPSUM (CALCIUM SULFATE) (CAS 7778-18-9)	TWA	5 mg/m <sup>3</sup>	Respirable.
IRON OXIDE (CAS 1309-37-1)	TWA	10 mg/m <sup>3</sup>	Total
		5 mg/m <sup>3</sup>	Dust and fume.
KAOLIN† (CAS 92704-41-1)	TWA	5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Total
PORTLAND CEMENT (CAS 65997-15-1)	TWA	5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Total

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Exposure guidelines</b>	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.
<b>Appropriate engineering controls</b>	When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Safety shower/eye wash fountain must be readily available in the workplace area (29 CFR 1910.151(c)).
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.
<b>Other</b>	Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)).
<b>Respiratory protection</b>	A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

<b>Appearance</b>	Powder
<b>Physical state</b>	Solid.
<b>Form</b>	Solid
<b>Color</b>	Light grey to white
<b>Odor</b>	Low odor
<b>Odor threshold</b>	Not available.
<b>pH</b>	10 - 12
<b>Melting point/freezing point</b>	2642 °F (1450 °C) estimated

<b>Initial boiling point and boiling range</b>	Not applicable
<b>Flash point</b>	Not applicable
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not applicable
<b>Flammability limit - upper (%)</b>	Not applicable
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not applicable
<b>Vapor density</b>	Not applicable
<b>Relative density</b>	2.7 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	0.2 % @ 22°C
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not applicable
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	3.02 g/cm <sup>3</sup> estimated
<b>Explosive properties</b>	Not explosive.
<b>Flash point class</b>	Not flammable
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	0 % estimated
<b>Specific gravity</b>	2.7
<b>VOC</b>	0 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	Reacts with water (normal condition of use).
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Not expected under normal conditions of use.
<b>Conditions to avoid</b>	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Exposure to moisture.
<b>Incompatible materials</b>	Acids.
<b>Hazardous decomposition products</b>	May include and are not limited to: calcium oxide and sulfur dioxide.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
<b>Eye contact</b>	Causes serious eye damage.
<b>Ingestion</b>	May be harmful if swallowed. May cause irritation of the gastrointestinal tract.

**Symptoms related to the physical, chemical and toxicological characteristics**

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

**Information on toxicological effects**

**Acute toxicity**

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
Pacific Stone		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	5850 mg/l/4h
<b>Oral</b>		
LD50	Rat	4597 mg/kg

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
FORMALDEHYDE-NAPHTHALENESULFONIC ACID POLYMER SODIUM SALT (CAS 9084-06-4)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	> 5200 mg/kg
GYPSUM (CALCIUM SULFATE) (CAS 7778-18-9)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	> 1581 mg/kg
IRON OXIDE (CAS 1309-37-1)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	> 10000 mg/kg
KAOLIN† (CAS 92704-41-1)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	2000.0001 mg/kg
TITANIUM DIOXIDE‡ (CAS 13463-67-7)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	> 10000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
<b>Serious eye damage/eye irritation</b>	Causes serious eye damage.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

## Carcinogenicity

Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

Respirable titanium dioxide from occupational sources has been classified by IARC as a possible lung carcinogen to humans. Human studies do not suggest an association between occupational exposure to titanium dioxide and an increased risk for cancer. Evidence showed that high concentrations caused respiratory tract cancer in rats exposed by inhalation and intratracheal instillation.

### IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	1 Carcinogenic to humans.
IRON OXIDE (CAS 1309-37-1)	3 Not classifiable as to carcinogenicity to humans.
TITANIUM DIOXIDE‡ (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	Cancer
--	--------

### US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	Known To Be Human Carcinogen.
--	-------------------------------

<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs (lung) through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Large quantities of this product may be harmful to aquatic life due to high pH.

Product		Species	Test Results
Pacific Stone			
<b>Aquatic</b>			
Algae	IC50	Algae	1909.1527 mg/L, 72 Hours estimated
Crustacea	EC50	Daphnia	19.1561 mg/L, 48 Hours estimated
<i>Acute</i>			
Fish	LC50	Fish	8397.6602 mg/l, 96 hours estimated
<b>Components</b>		<b>Species</b>	<b>Test Results</b>
CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Zebra danio (Danio rerio)	> 10000 mg/l, 96 Hours OECD SIDS
GYPHUM (CALCIUM SULFATE) (CAS 7778-18-9)			
<b>Aquatic</b>			
Fish	LC50	Fish	2980 mg/l, 96 Hours
KAOLIN† (CAS 92704-41-1)			
<b>Aquatic</b>			
Algae	IC50	Algae	100.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1.0001 mg/L, 48 Hours
TITANIUM DIOXIDE‡ (CAS 13463-67-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential****Mobility in soil** No data available.**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.**13. Disposal considerations****Disposal instructions** Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.**Local disposal regulations** Dispose in accordance with all applicable regulations.**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. Transport information****DOT**

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not available.**15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Cancer  
lung effects  
immune system effects  
kidney effects**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes**Classified hazard categories** Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.



## US state regulations

### California Proposition 65



**WARNING:** This product can expose you to chemicals including CRYSTALLINE SILICA (QUARTZ), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Listed: October 1, 1988

TITANIUM DIOXIDE‡ (CAS 13463-67-7) Listed: September 2, 2011

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

TITANIUM DIOXIDE‡ (CAS 13463-67-7)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** December-15-2017

**Revision date** August-22-2018

**Version #** 02

**HMIS® ratings** Health: 3\*  
Flammability: 0  
Physical hazard: 0

**NFPA ratings** Health: 3  
Flammability: 0  
Instability: 0

**Disclaimer** This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

**Revision information** Regulatory information: California Proposition 65  
Regulatory information: US federal regulations  
HazReg Data: International Inventories